

# C300 HIGH SOLIDS CONTACT ADHESIVE

DATA SHEET

Tensorbond®



As part of our **CONSTRUCTION** range, **TensorBond® C300** is a non-flammable contact adhesive with good initial tack, good combinability and high solids.

## PRODUCT DESCRIPTION

**TensorBond® C300** is designed for laminate and general bonding to many substrates using traditional bulk liquid spray equipment.

### ADVANTAGES

- Excellent coverage
- Bonds, metal, plastics, wood, rubber, and porous or non-porous surfaces
- 80% of final strength achieved immediately
- Full strength achieved in 24 hours
- Fast drying with long open time (30-45 minutes)

## DIRECTIONS FOR USE

- Should be applied to each surface, allowed to dry, (until non-transferable to finger) then bonded under pressure. When brushing, multiple coats may be required on porous surfaces. When spraying – use of Devilbiss JGA 510 gun with E or FF tip and needle or Binks model 2001 or 95 gun – 66 or 63C fluid nozzle and needle to similar equipment is satisfactory. Aluminum or copper components should be avoided. To achieve efficient coverage, adhesive should be applied at 3 dry grams per square foot.
- If the spray tip clogs, unscrew the spray tip from the gun and clean with solvent such as lacquer thinner or acetone. Do not use a pin on the spray tip orifice.

### CANISTER STORAGE/CHANGE OVER

- Turn valve on canister into the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister. Reconnect the spray hose to a canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean. If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quinlobal.com](http://www.quinlobal.com)

QUIN  
GLOBAL

Tensorbond®

# C300

## HIGH SOLIDS CONTACT ADHESIVE

DATA SHEET

**Tensorbond®**

### CHEMICAL TECHNICAL DATA

#### TYPICAL PROPERTIES

- Viscosity 350 cps
- Total Solids 21%-29%
- Color Natural, Green, or Red
- Shelf Life 12 months
- Solvent Non-Flammable
- Coverage 275.5 bonded sq ft per gallon at 2.0 dry grams per sq ft

#### PACKAGING

- 1 Gallon Can
- 5 Gallon Pail
- 55 Gallon Drum

### STORAGE

#### HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do Not store at temperatures over 120°F.
- Avoid exposure to direct sunlight.
- Do Not store directly on concrete floor.
- For optimum performance, store at 18°C during use, but must always be above 50°F.
- When connected, keep valve open and hose pressurised at all times.
- Do Not close valve until ready to connect to new cylinder.
- Release pressure in hose before disconnection.
- Always test product to determine suitability for your particular application prior to use in production.

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

**QUIN GLOBAL US**

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quinlobal.com](http://www.quinlobal.com)

**QUIN**  
GLOBAL

**Tensorbond®**

# Tensorbond

## SAFETY DATA SHEET Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

### 1. Identification

#### Product identifier

**Product name** Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

**Product number** USA

#### Recommended use of the chemical and restrictions on use

**Application** Solvent-based Adhesive

#### Details of the supplier of the safety data sheet

**Supplier** Quin Global USA  
5710 F St.  
Omaha, NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

#### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

### 2. Hazard(s) identification

#### Classification of the substance or mixture

**Physical hazards** Not Classified

**Health hazards** Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

**Environmental hazards** Not Classified

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

#### Label elements

##### Hazard symbols



**Signal word**

Danger

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

<b>Hazard statements</b>	H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
<b>Precautionary statements</b>	P260 Do not breathe vapor/ spray. P301+P310 If swallowed: Immediately call a poison center/ doctor. P302+P352 If on skin: Wash with plenty of water. P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/ doctor if you feel unwell.
<b>Contains</b>	Methylene Chloride

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Methylene Chloride</b>	<b>60-100%</b>
CAS number: 75-09-2	
<b>Classification</b>	
Acute Tox. 3 - H301	
Acute Tox. 4 - H312	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Carc. 2 - H351	
STOT SE 3 - H335, H336	
STOT RE 2 - H373	

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

### Most important symptoms and effects, both acute and delayed

**Inhalation** May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.

**Ingestion** Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

**Skin contact** May be absorbed through the skin. Product has a defatting effect on skin. The product is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.

**Eye contact** Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

## 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** Extinguish with Carbon Dioxide, Dry Chemical and Foam.

### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep container tightly closed. Keep only in the original container.

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

### 8. Exposure controls/Personal protection

#### Control parameters

#### Occupational exposure limits

#### Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

#### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.

#### Eye/face protection

Wear chemical splash goggles.

#### Hand protection

Use protective gloves.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Liquid.
Color	Clear. Red.
Odor	Organic solvents.
Initial boiling point and range	Not determined.
Flash point	None.
Upper/lower flammability or explosive limits	None.
Vapor pressure	Not determined.
Vapor density	Not determined.
Relative density	1.22

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

**Solubility(ies)** Negligibly soluble in water

### 10. Stability and reactivity

**Stability** Stable at normal ambient temperatures and when used as recommended.

**Possibility of hazardous reactions** Will not polymerize.

**Conditions to avoid** Avoid contact with the following materials: Oxidizing agents. Reducing agents.

**Materials to avoid** None known.

**Hazardous decomposition products** Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 131.96093956

##### Acute toxicity - dermal

ATE dermal (mg/kg) 1,451.57033518

#### Toxicological information on ingredients.

##### Methylene Chloride

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 52.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

##### Carcinogenicity

**Carcinogenicity** Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

**Target organ for carcinogenicity** Tumerigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors

**IARC carcinogenicity** IARC Group 2B Possibly carcinogenic to humans.

**NTP carcinogenicity** Reasonably anticipated to be a human carcinogen.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Inhalation - May cause damage to organs through prolonged or repeated exposure  
-Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure -Liver, blood.

**General information** RTECS: PA8050000

### 12. Ecological information

### 13. Disposal considerations

**Waste treatment methods**

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**UN Number**

**UN No. (DOT)** UN 1593

**UN proper shipping name**

**Proper shipping name (DOT)** UN 1593 Dichloromethane, 6.1

**Transport hazard class(es)**

**TDG class** 6.1

**IMDG Class** 6.1

**ICAO class/division** 6.1

**Transport labels**



**Packing group**

**Packing group (International)** Not applicable.

**TDG Packing Group** III

**IMDG packing group** III

**ICAO packing group** III

**DOT packing group** III

### 15. Regulatory information

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).
<b>Guidance</b>	CHIP for everyone HSG228. Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

### US Federal Regulations

**CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**  
Present.

**SARA 313 Emission Reporting**  
Present.

**SARA (311/312) Hazard Categories**  
Present.

### US State Regulations

**California Proposition 65 Carcinogens and Reproductive Toxins**  
Present.

### Inventories

**US - TSCA**  
Present.

### 16. Other information

<b>Revision date</b>	10/10/2019
<b>Revision</b>	5
<b>Supersedes date</b>	10/10/2019
<b>SDS No.</b>	20558
<b>Hazard statements in full</b>	H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.
<b>ACA HMIS Health rating.</b>	Moderate hazard. (2)
<b>ACA HMIS Flammability rating.</b>	Will not burn. (0)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B

### DIRECTIONS FOR USE

## Tensorbond C300 Non Flam Sprayable Liquid Contact Adhesive

### PRODUCT LOGO

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application