

# LB90 PREMIUM HIGH-TEMPERATURE FLAMMABLE CONTACT ADHESIVE

DATA SHEET  
**Tensorbond**

## PRODUCT DESCRIPTION

**TensorBond® LB90** is a premium flammable high performance, sprayable industrial contact adhesive formulated for laminating contact bonding.

**TensorBond® LB90** is designed for laminate and general bonding to many substrates via traditional bulk spray equipment.

## APPLICATIONS

- Bonds laminate to particle board; including melamine, metals and most plastics
- Also bonds: leather, veneers, fabrics, upholstery, foam, cork, fiberglass and many plastics
- Laminating flexible material in nearly any application

## DIRECTIONS FOR USE

- **TensorBond® LB90** should be applied to both surfaces to be bonded, 80% to 100% coverage. Allow to dry (until dry to the touch) parts should be mated under pressure. Apply pressure with a hand laminate roller or nip roller. Bonds should be made as soon practical. If adhesive is left to dry for over 30 minutes, parts should be recoated. Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately although ultimate strength is achieved in 1-3 days. Store away from heat, flames or other sources of ignition.

### Canister System Recommendation:

- If you'd like to save time and increase your efficiency, Quin Global recommends using the Tensorgrip canister system – a pre-pressurized canister of adhesive. Ask us about this adhesive in a canister.

**QUIN GLOBAL US**

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quinglobal.com](http://www.quinglobal.com)

**QUIN**  
GLOBAL

**Tensorbond**

# LB90 PREMIUM HIGH-TEMPERATURE FLAMMABLE CONTACT ADHESIVE

DATA SHEET  
**Tensorbond**

## BENEFITS

- Industrial version of Tensorbond aircraft contact adhesive
- Fast. High Tack
- Excellent coverage
- 80% of final strength achieved immediately
- Full strength achieved in 24 hours
- Fast drying with long open time (30-45 minutes)
- Excellent green strength and high heat resistance
- High temperature resistant
- No ODS (Ozone Depleting Substances)
- No chlorinated solvents

## CHEMICAL TECHNICAL DATA

### TYPICAL PROPERTIES

- |                |                      |
|----------------|----------------------|
| • VOC Content: | 343 gm/L             |
| • Solids:      | 17-22% (Liquid)      |
| • Viscosity:   | 100-150 cps          |
| • Appearance:  | Clear/Neutral or Red |
| • Shelf Life:  | 8 Months             |
| • Solvent:     | Flammable            |
| • Weight:      | 7lb/gal              |
| •              |                      |

### PACKAGING

- 1 gallon can
- 5 gallon pail
- 55 gallon drum

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

**QUIN GLOBAL US**

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quinglobal.com](http://www.quinglobal.com)

**QUIN**  
GLOBAL

**Tensorbond**

# Tensorbond

## SAFETY DATA SHEET Tensorbond LB90 Neoprene Contact Adhesive

### 1. Identification

#### Product identifier

**Product name** Tensorbond LB90 Neoprene Contact Adhesive

**Product number** USA

#### Recommended use of the chemical and restrictions on use

**Application** Solvent-based Adhesive

#### Details of the supplier of the safety data sheet

**Supplier** Quin Global USA  
5710 F St.  
Omaha, NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

#### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300 (Mon - Fri) 09:00 - 16:00

### 2. Hazard(s) identification

#### Classification of the substance or mixture

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Repr. 2 - H361fd STOT SE 3 - H336 STOT RE 2 - H373

**Environmental hazards** Aquatic Chronic 2 - H411

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

#### Label elements

##### Pictogram



**Signal word**

Danger

## Tensorbond LB90 Neoprene Contact Adhesive

### Hazard statements

H225 Highly flammable liquid and vapor.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352 If on skin: Wash with plenty of water.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P403+P235 Store in a well-ventilated place. Keep cool.

### Contains

Acetone, n-Hexane, Toluene, 2-Propanol

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Substances

#### Mixtures

<b>Acetone</b>	<b>30-60%</b>
CAS number: 67-64-1	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	

## Tensorbond LB90 Neoprene Contact Adhesive

<b>n-Hexane</b>	<b>10-30%</b>
CAS number: 110-54-3	
M factor (Acute) = 1	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Repr. 2 - H361f	
STOT SE 3 - H336	
STOT RE 2 - H373	
Aquatic Chronic 2 - H411	
<b>Toluene</b>	<b>10-30%</b>
CAS number: 108-88-3	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
<b>2-Propanol</b>	<b>1-5%</b>
CAS number: 67-63-0	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The Full Text for all Hazard Statements are Displayed in Section 16.

#### 4. First-aid measures

##### Description of first aid measures

##### **General information**

Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.

## Tensorbond LB90 Neoprene Contact Adhesive

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

### Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.
<b>Ingestion</b>	Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Central nervous system depression. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>Skin contact</b>	May be absorbed through the skin. Product has a defatting effect on skin. The liquid is irritating to eyes and skin. Remove contaminated clothing. A single exposure may cause the following adverse effects: Dryness and/or cracking.
<b>Eye contact</b>	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

#### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

## Tensorbond LB90 Neoprene Contact Adhesive

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## 8. Exposure Controls/personal protection

### Control parameters

#### Occupational exposure limits

##### **Acetone**

Long-term exposure limit (8-hour TWA): ACGIH 500 ppm

Short-term exposure limit (15-minute): ACGIH 750 ppm

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m<sup>3</sup>

Ceiling exposure limit: NIOSH: National Institute of Occupational Safety and Health 250 ppm 590 mg/m<sup>3</sup> vapour

##### **n-Hexane**

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

Sk

Ceiling Value: OSHA\_TRANS 500 ppm 1800 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): OSHA 50 ppm 180 mg/m<sup>3</sup>

##### **Toluene**

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm

A4

Short-term exposure limit (15-minute): NIOSH: National Institute of Occupational Safety and Health 150 ppm 560 mg/m<sup>3</sup>

Ceiling Value: OSHA 300 ppm

Long-term exposure limit (8-hour TWA): OSHA 200 ppm

##### **2-Propanol**

## Tensorbond LB90 Neoprene Contact Adhesive

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m<sup>3</sup>

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

Sk = Danger of cutaneous absorption.

A4 = Not Classifiable as a Human Carcinogen.

### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

#### Eye/face protection

Wear chemical splash goggles.

#### Hand protection

Use protective gloves.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance	Liquid.
Color	Clear. Amber.
Odor	Organic solvents.
Melting point	Not determined.
Initial boiling point and range	55°C/131°F @ 1013.25 mbar
Flash point	-26°C/-14.8°F
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.2 g/100 g Upper flammable/explosive limit: 13 g/100 g
Vapour pressure	233 hPa @ °C
Relative density	0.82
Bulk density	Not determined.



## Tensorbond LB90 Neoprene Contact Adhesive

<b>Solubility(ies)</b>	Negligibly soluble in water
<b>Auto-ignition temperature</b>	240°C/464°F
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 343 g/l.

### 10. Stability and reactivity

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
<b>Possibility of hazardous reactions</b>	Vapors may form explosive mixture with air.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
<b>Materials to avoid</b>	Oxidizing agents. Bases. Strong acids.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Hydrogen chloride (HCl). Nitrous gases (NO <sub>x</sub> ).

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 595.23809524

##### Acute toxicity - dermal

ATE dermal (mg/kg) 1,309.52380952

##### Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 13.0952381

#### Toxicological information on ingredients.

##### Acetone

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 500.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 20,000.0

Species Rabbit

ATE dermal (mg/kg) 1,100.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l) 76.0

Species Rat

## Tensorbond LB90 Neoprene Contact Adhesive

ATE inhalation (vapours  
mg/l) 11.0

### Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness

Inhalation Mucosal irritations. Absorption.

Ingestion Irritating. May cause nausea, stomach pain and vomiting. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin Contact This product is moderately irritating. May be absorbed through the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact This product is strongly irritating. Risk of corneal clouding.

Route of entry Inhalation Skin and/or eye contact

Target Organs Eyes

### n-Hexane

#### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 25,000.0

Species Rat

ATE oral (mg/kg) 500.0

#### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub>  
mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 1,100.0

#### Acute toxicity - inhalation

Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l) 171.6

Species Rat

ATE inhalation (vapours  
mg/l) 11.0

#### Reproductive toxicity

Reproductive toxicity -  
fertility Suspected of damaging fertility.

### Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness

Target organs Central nervous system

### Specific target organ toxicity - repeated exposure

## Tensorbond LB90 Neoprene Contact Adhesive

<b>STOT - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Target organs</b>	Central nervous system
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>General information</b>	
	After absorption. Tiredness. Narcosis. After long term exposure to the chemical: CNS disorders, paralysis symptoms. (It generally applies to aliphatic hydrocarbons with 6 - 18 carbon atoms that they cause pneumonia, in some cases also pulmonary edema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar.)) Absorbtion of large quantities may cause: Narcosis. Possible risk of adverse reproductive effects.
<b>Inhalation</b>	May cause drowsiness or dizziness. Vapors irritate the respiratory system.
<b>Ingestion</b>	Irritating. May cause nausea, stomach pain and vomiting.
<b>Skin Contact</b>	The product is irritating to eyes and skin.
<b>Eye contact</b>	Risk of corneal clouding.
<b>Route of entry</b>	Inhalation Skin and/or eye contact
<b>Target Organs</b>	Eyes Skin Respiratory system, lungs Central nervous system Peripheral nervous system

### Toluene

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 636.0

**Species** Rat

**ATE oral (mg/kg)** 500.0

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 12,124.0

**Species** Rabbit

**ATE dermal (mg/kg)** 1,100.0

#### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 28.1

**Species** Rat

**ATE inhalation (vapours mg/l)** 11.0

### 2-Propanol

#### Acute toxicity - oral

## Tensorbond LB90 Neoprene Contact Adhesive

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,045.0

**Species** Rat

**ATE oral (mg/kg)** 500.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 12,800.0

**Species** Rabbit

**ATE dermal (mg/kg)** 1,100.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 15,981.7

**Species** Rat

**ATE inhalation (vapours mg/l)** 11.0

**Skin corrosion/irritation**

**Animal data** Slightly irritating.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Irritating.

**Respiratory sensitization**

**Respiratory sensitisation** No information available.

**Skin sensitization**

**Skin sensitisation** No information available.

**Carcinogenicity**

**Carcinogenicity** Does not contain any substances known to be carcinogenic.

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** May cause drowsiness or dizziness

**Aspiration hazard**

**Aspiration hazard** No data available.

**Medical Symptoms** High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Central nervous system depression. Liver damage.

### 12. Ecological Information

### 13. Disposal considerations

### Waste treatment methods

## Tensorbond LB90 Neoprene Contact Adhesive

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**Air transport notes** 1. 5L, 2. 60L

**UN Number**

**UN No. (DOT)** 1133 or Limited Quantity <5L

**UN No. (ICAO)** 1133

**UN proper shipping name**

**Proper shipping name (DOT)** Adhesives

**Transport hazard class(es)**

**DOT hazard class** 3

**Transport labels**



**Packing group**

II

### 15. Regulatory information

**Inventories**

**US - TSCA**

Present.

**Toluene**

**n-Hexane**

**Acetone**

### 16. Other information

**Revision date** 11/10/2015

**Revision** 3

**Supersedes date** 8/21/2015

**SDS No.** 21228

## Tensorbond LB90 Neoprene Contact Adhesive

<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
<b>ACA HMIS Health rating.</b>	Moderate hazard. (2)
<b>ACA HMIS Flammability rating.</b>	Ignites easily. (3)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application