

# C17 EDGE STIFFENER

DATA SHEET  
**TensorGrip**



As part of our **CONSTRUCTION** range, **C17** is a web spray coating designed for use in applications using the substrates listed.

## PRODUCT DESCRIPTION

**TensorGrip C17** is a fast-drying edge stiffener for fiberglass board, with the speed of application and convenience of a canister delivery system.

### ADVANTAGES

- Fast drying solvent system allows faster processing times and quicker secondary finishing
- Compatible with most adhesives used for wrapping panels
- Non-flammable solvent, zero VOC product
- No moisture to create mold or mildew

## DIRECTIONS FOR USE

- **TensorGrip C17** is designed as a portable, self-contained spray system for field or shop applications.
- Suggested tip: 400050
- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Hold applicator perpendicular to substrate, 2-4 inches away
- Spray the edge surface with a heavy coat allowing the adhesive to soak into the insulation. Let dry for 10 minutes or until it appears dry.
- Continue applying additional coats to get the stiffness desired.
- Wait 10 minutes or longer after the last coat before finishing off the panel.
- Canister system will spray adequately above 60° F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

### CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.

**QUIN GLOBAL US**

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quiringlobal.com](http://www.quiringlobal.com)

**QUIN**  
GLOBAL

**TensorGrip**

### CHEMICAL TECHNICAL DATA

#### TYPICAL PROPERTIES

- Total Solids 22-28%
- VOC Content 0 g/L
- Color Clear
- System Flammability Non-Flammable Adhesive; Non-Flammable Propellant
- Solvent System Methylene Chloride
- Dry time 2-10 mins dependent on temp & humidity
- Open time Long
- Shelf Life 18 months from date of manufacture

#### PACKAGING

- 7L Disposable Canister
- 22L Disposable Canister
- 108L Returnable Canister

### STORAGE

#### HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

# SAFETY DATA SHEET

## TensorGrip C17 Edge Stiffener

### 1. Identification

#### Product identifier

**Product name** TensorGrip C17 Edge Stiffener  
**Product number** USA

#### Recommended use of the chemical and restrictions on use

**Application** Canister Spray Adhesive

#### Details of the supplier of the safety data sheet

**Supplier** Quin Global  
 5710 F St  
 Omaha NE 68117  
 (402) 731 3636  
 (402) 731 1473  
 marketing.us@quin-global.com

#### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

### 2. Hazard(s) identification

#### Classification of the substance or mixture

**Physical hazards** Press. Gas, Compressed - H280  
**Health hazards** Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373  
**Environmental hazards** Not Classified

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

#### Label elements

##### Pictogram



##### Signal word

Danger

##### Hazard statements

H280 Contains gas under pressure; may explode if heated.  
 H301 Toxic if swallowed.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.

## TensorGrip C17 Edge Stiffener

<b>Precautionary statements</b>	<p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P301+P310 If swallowed: Immediately call a poison center/ doctor.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 If exposed or concerned: Get medical advice/ attention.</p>
---------------------------------	--

<b>Contains</b>	Methylene Chloride
-----------------	--------------------

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Methylene Chloride</b>	<b>60-100%</b>
CAS number: 75-09-2	
<b>Classification</b>	
Acute Tox. 3 - H301	
Acute Tox. 4 - H312	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Carc. 2 - H351	
STOT SE 3 - H335, H336	
STOT RE 2 - H373	

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

#### Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.
-------------------	---

## TensorGrip C17 Edge Stiffener

<b>Ingestion</b>	Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>Skin contact</b>	May be absorbed through the skin. Product has a defatting effect on skin. The product is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.
<b>Eye contact</b>	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

### 5. Fire-fighting measures

#### Special hazards arising from the substance or mixture

**Specific hazards** Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

#### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

#### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

### 7. Handling and storage

#### Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

### 8. Exposure Controls/personal protection

#### Control parameters

#### Occupational exposure limits

## TensorGrip C17 Edge Stiffener

### Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.

#### Eye/face protection

Wear chemical splash goggles.

#### Hand protection

Use protective gloves.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance	Aerosol.
Relative density	1.3
Volatile organic compound	This product contains a maximum VOC content of 0 g/l.

## 10. Stability and reactivity

Stability	Stable at normal ambient temperatures and when used as recommended.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Nitrous gases (NO <sub>x</sub> ).

## 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity - oral

ATE oral (mg/kg)	149.25
------------------	--------

## TensorGrip C17 Edge Stiffener

### Acute toxicity - dermal

ATE dermal (mg/kg) 1,641.79

### Toxicological information on ingredients.

#### Methylene Chloride

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 52.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

##### Carcinogenicity

Carcinogenicity Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies

Target organ for carcinogenicity Tumerigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

##### Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness

##### Specific target organ toxicity - repeated exposure

STOT - repeated exposure Inhalation - May cause damage to organs through prolonged or repeated exposure  
-Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure  
-Liver, blood.

General information RTECS: PA8050000

### 12. Ecological Information

### 13. Disposal considerations

### Waste treatment methods

## TensorGrip C17 Edge Stiffener

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**Air transport notes** 1. <75kg, 2. <150kg

#### UN Number

**UN No. (TDG)** 3500

**UN No. (ICAO)** 3500

**UN No. (DOT)** 3500

#### UN proper shipping name

**Proper shipping name (TDG)** Chemical Under Pressure, N.O.S. (Air, Compressed)

**Proper shipping name (DOT)** Chemical Under Pressure, N.O.S. (Air, Compressed)

#### Transport hazard class(es)

**TDG class** 2

**TDG label(s)** 2.2

#### Transport labels



#### Packing group

Not applicable.

### 15. Regulatory information

### 16. Other information

**Revision date** 12/1/2017

**Revision** 5

**Supersedes date** 8/20/2015

**SDS No.** 22176

**Hazard statements in full** H280 Contains gas under pressure; may explode if heated.  
 H301 Toxic if swallowed.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure.

**ACA HMIS Health rating.** Moderate hazard. (2)

**ACA HMIS Flammability rating.** Will not burn. (0)



## TensorGrip C17 Edge Stiffener

**ACA HMIS Physical hazard rating.** Normally stable. (0)

**ACA HMIS Personal protection rating.** B

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.