

# L20 CA COMPLIANT, LOW VOC CONTACT ADHESIVE

DATA SHEET  
**TensorGrip®**



As part of our **WOODWORKING** range, L20 is a web spray adhesive designed for use in fabricating countertops, cabinets and doors using the substrates listed above.

## PRODUCT DESCRIPTION

TensorGrip® L20 is formulated to achieve a successful, lasting bond to standard laminates and a range of other substrates while complying with strict California VOC regulations. Formulated with CO-REZ Technology, which is an exceptional formulation incorporating a highly engineered resin and gas matrix. The result: Greater Coverage from Less Canister Weight.

### ADVANTAGES

- High tack
- Fast dry with excellent initial bond
- Good heat resistance (up to 200°F)
- High-strength
- Low VOC
- SCAQMD Rule 1168 Compliant
- Qualifies for LEED 3.2, 4.1, 4.4

## DIRECTIONS FOR USE

- TensorGrip® L20 is designed as a portable, self-contained spray system for field or shop applications.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60° F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

### CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quin-global.com

QUIN  
GLOBAL

TensorGrip®

# L20 CA COMPLIANT, LOW VOC CONTACT ADHESIVE

DATA SHEET  
**Tensorgrip**<sup>®</sup>

## CHEMICAL TECHNICAL DATA

### TYPICAL PROPERTIES

- Total Solids 31-37%
- VOC Content 45g/l (Canister), 35.9% by weight (Aerosols)
- Color Clear, Red
- System Flammability Flammable Adhesive, Non-Flammable Propellant (Canister) Flammable Adhesive and Propellant (Aerosol)
- Solvent System Methyl Acetate
- Dry time 2-4 mins dependent on temp & humidity
- Open time Long
- Shelf Life 18 months from date of manufact

### PACKAGING

- 650ml Aerosols
- 22L Disposable Canister
- 108L Returnable Canister
- 216L Returnable Canister

## STORAGE

### HANDLING & STORAGE

- Consult Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

**QUIN GLOBAL US**

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | [info.us@quin-global.com](mailto:info.us@quin-global.com) | [www.quin-global.com](http://www.quin-global.com)

**QUIN**  
GLOBAL

**Tensorgrip**<sup>®</sup>



## SAFETY DATA SHEET

### Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

#### 1. Identification

##### Product identifier

**Product name** Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

**Product number** USA

##### Recommended use of the chemical and restrictions on use

**Application** Aerosol Spray Adhesive

##### Details of the supplier of the safety data sheet

**Supplier** Tensorgrip  
5710 F St  
Omaha NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

##### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Aerosol 1 - H222


**Health hazards** Acute Tox. 4 - H302 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373

**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

##### Label elements

##### Pictogram



##### Signal word

Danger

##### Hazard statements

H302+H332 Harmful if swallowed or if inhaled.  
H222 Extremely flammable aerosol.  
H319 Causes serious eye irritation.  
H361f Suspected of damaging fertility.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

<b>Precautionary statements</b>	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 If exposed or concerned: Get medical advice/ attention.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.</p>
<b>Supplemental label information</b>	<p>AT(o) 15.0% of the mixture consists of ingredient(s) of unknown acute oral toxicity.</p> <p>Contains 6.671 % of components with unknown hazards to the aquatic environment.</p>
<b>Contains</b>	Methyl Acetate, Propane, Isobutane, n-Hexane

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Methyl Acetate</b> <span style="float: right;"><b>30-60%</b></span> CAS number: 79-20-9
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336
<b>Propane</b> <span style="float: right;"><b>10-25%</b></span> CAS number: 74-98-6
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas, Liquefied - H280 Acute Tox. 4 - H332 Simple Asphyxiant - USH03
<b>Isobutane</b> <span style="float: right;"><b>10-25%</b></span> CAS number: 75-28-5
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas, Compressed - H280

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

<b>n-Hexane</b> <span style="float: right;"><b>5-10%</b></span> CAS number: 110-54-3 M factor (Acute) = 1
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

#### Most important symptoms and effects, both acute and delayed

<b>General information</b>	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
<b>Ingestion</b>	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

**Eye contact** Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards** Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

#### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

#### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

#### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

### 7. Handling and storage

#### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

#### Specific end uses(s)

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

### 8. Exposure controls/Personal protection

#### Control parameters

#### Occupational exposure limits

##### **Methyl Acetate**

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m<sup>3</sup>

##### **Propane**

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 1800 mg/m<sup>3</sup> 1000 ppm

Long-term exposure limit (8-hour TWA): OSHA 1800 ppm 1000 mg/m<sup>3</sup>

##### **Isobutane**

Long-term exposure limit (8-hour TWA): ACGIH 1000 ppm

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 800 ppm 1900 mg/m<sup>3</sup>

##### **n-Hexane**

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

Sk

Ceiling Value: OSHA\_TRANS 500 ppm 1800 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): OSHA 50 ppm 180 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

Sk = Danger of cutaneous absorption.

#### Exposure controls

##### **Protective equipment**



##### **Appropriate engineering controls**

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

##### **Eye/face protection**

Wear chemical splash goggles.

##### **Hand protection**

Use protective gloves.

##### **Other skin and body protection**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

##### **Hygiene measures**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

##### **Respiratory protection**

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

<b>Appearance</b>	Aerosol.
<b>Color</b>	Clear. Red.
<b>Odor</b>	Organic solvents.
<b>Initial boiling point and range</b>	-42.1°C (-43.8°F)
<b>Flash point</b>	-104°C/-155°F Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Upper flammable/explosive limit: 9.5 g/100 g Lower flammable/explosive limit: 2.1 g/100 g
<b>Relative density</b>	~ .928
<b>Solubility(ies)</b>	Negligibly soluble in water
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 35.9% by weight .

### 10. Stability and reactivity

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Aldehydes. Halogenated hydrocarbons.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 924.11

##### Acute toxicity - dermal

ATE dermal (mg/kg) 2,391.82

##### Acute toxicity - inhalation

ATE inhalation (gases ppm) 30,000.0

ATE inhalation (vapours mg/l) 18.04

#### Toxicological information on ingredients.

##### Methyl Acetate

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 500.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0



## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 49.28

Species Rat

ATE inhalation (vapours mg/l) 11.0

### Propane

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> gases ppmV) 1,442.0

Species Rat

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 1,442.0

Species Rat

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

### Isobutane

Toxicological effects No information available.

### Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Inhalation Suffocation (asphyxiant) hazard

Skin Contact Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Eye contact Spray will evaporate and cool quickly and may cause frostbite or cold burns if in contact with skin.

### n-Hexane

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 25,000.0

Species Rat

ATE oral (mg/kg) 500.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rabbit

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

<b>ATE dermal (mg/kg)</b>	1,100.0
<b><u>Acute toxicity - inhalation</u></b>	
<b>Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)</b>	171.6
<b>Species</b>	Rat
<b>ATE inhalation (vapours mg/l)</b>	11.0
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Suspected of damaging fertility.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	May cause drowsiness or dizziness
<b>Target organs</b>	Central nervous system
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Target organs</b>	Central nervous system
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b><u>General information</u></b>	
	After absorption. Tiredness. Narcosis. After long term exposure to the chemical: CNS disorders, paralysis symptoms. (It generally applies to aliphatic hydrocarbons with 6 - 18 carbon atoms that they cause pneumonia, in some cases also pulmonary edema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar.)) Absorption of large quantities may cause: Narcosis. Possible risk of adverse reproductive effects.
<b>Inhalation</b>	May cause drowsiness or dizziness. Vapors irritate the respiratory system.
<b>Ingestion</b>	Irritating. May cause nausea, stomach pain and vomiting.
<b>Skin Contact</b>	The product is irritating to eyes and skin.
<b>Eye contact</b>	Risk of corneal clouding.
<b>Route of exposure</b>	Inhalation Skin and/or eye contact
<b>Target Organs</b>	Eyes Skin Respiratory system, lungs Central nervous system Peripheral nervous system

### 12. Ecological information

### 13. Disposal considerations

#### Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

### 14. Transport information

**Air transport notes** 1. <75kg, 2. <150kg

**UN Number**

**UN No. (ICAO)** 1950

**UN No. (DOT)** Limited Quantity <1L, Aerosol

**UN proper shipping name**

**Proper shipping name (TDG)** Chemical Under Pressure, Flammable, N.O.S.

**Proper shipping name (DOT)** Chemical Under Pressure, Flammable, N.O.S.

**Transport hazard class(es)**

**Transport labels**



**Packing group**

**Packing group (International)** Not applicable.

### 15. Regulatory information

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

**Guidance** CHIP for everyone HSG228.  
Workplace Exposure Limits EH40.  
Safety Data Sheets for Substances and Preparations.  
Approved Classification and Labelling Guide (Sixth edition) L131.

**US Federal Regulations**

**CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*n-Hexane*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

**SARA 313 Emission Reporting**

The following ingredients are listed or exempt:

*n-Hexane*

100%

**SARA (311/312) Hazard Categories**

Hazard

*Methyl Acetate*

Fire  
Acute  
Chronic  
Health hazard

*Propane*

Yes.

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

### *Isobutane*

Fire  
Pressure  
Hazard

### *n-Hexane*

Acute  
Chronic  
Health hazard  
Fire

## **US State Regulations**

### **California Proposition 65 Carcinogens and Reproductive Toxins**

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

#### *Methyl Acetate*

Present

#### *Propane*

Present

#### *Isobutane*

Present

#### *n-Hexane*

Present

### **New Jersey "Right To Know" List**

The following ingredients are listed or exempt:

#### *Methyl Acetate*

Present.

#### *Propane*

Present.

#### *Isobutane*

Present.

#### *n-Hexane*

Present.

### **Pennsylvania "Right To Know" List**

The following ingredients are listed or exempt:

#### *Methyl Acetate*

Present.

#### *Propane*

Present.

#### *Isobutane*

Present.

#### *n-Hexane*

Present.

## **Inventories**

### **Canada - DSL/NDSL**

The following ingredients are listed or exempt:

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

*Methyl Acetate*

Present.

*Propane*

DSL  
Present.

*n-Hexane*

DSL

### US - TSCA

Present.

*Methyl Acetate*

Present.

*Propane*

Present.

*n-Hexane*

Present.

### 16. Other information

<b>Revision date</b>	12/21/2018
<b>Revision</b>	13
<b>Supersedes date</b>	12/14/2018
<b>SDS No.</b>	20422
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapor. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. USH03 May displace oxygen and cause rapid suffocation
<b>ACA HMIS Health rating.</b>	Slight hazard. (1)
<b>ACA HMIS Flammability rating.</b>	Extremely flammable. (4)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B

### DIRECTIONS FOR USE

### PRODUCT LOGO

## Tensorgrip L20AA CA Compliant, Low VOC Contact Adhesive

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.