## F70N NON-FLAM PRESSURE-SENSITIVE ADHESIVE























As part of our **FOAM & FABRIC** range, **F70N** is a web spray adhesive designed for use in Domestic Furniture, Office Furniture and Mattress applications using the substrates listed.

## PRODUCT DESCRIPTION

**TensorGrip F70N** is a powerful pressure-sensitive adhesive developed specifically for pressure-sensitive bonding of porous and somewhat difficult substrates. TensorGrip F70N offers fast dry and high tack while still allowing repositionability and retaining lasting tackiness.

#### **ADVANTAGES**

- 100% Non-flammable
- VOC free
- Fast dry, high tack, long open time
- 170°F (77°C) temperature resistant

- 80% of final strength immediately
- Very aggressive PSA
- Repositionable
- Excellent green strength and high heat resistance
- No ODS (Ozone Depleting Substances)

## DIRECTIONS FOR USE

- TensorGrip F70N is designed as a portable, selfcontained spray system for field or shop applications.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage. Spraying both surfaces will result in a stronger, more permanent bond.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical. Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days
- Canister system will spray adequately above 60° F.
   Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

### CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.





# NON-FLAM PRESSURE-SENSITIVE ADHESIVE Tensorum

## CHEMICAL TECHNICAL DATA

#### TYPICAL PROPERTIES

Total Solids
 VOC Content
 Color
 Blue, Clear

System Flammability 100% Non-Flammable
 Solvent System Methylene Chloride

Dry time 3-5 mins dependent on temp & humidity
Open time Long

Shelf Life 18 months from date of manufacture

#### **PACKAGING**

22L Disposable Canister
 108L Returnable Canister
 216L Returnable Canister

## **STORAGE**

#### HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- · Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.



