



## SAFETY DATA SHEET

### Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

#### 1. Identification

##### Product identifier

**Product name** Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

**Product number** USA

##### Recommended use of the chemical and restrictions on use

**Application** Canister Spray Adhesive

##### Details of the supplier of the safety data sheet

**Supplier** Tensorgrip  
5710 F St  
Omaha NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

##### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

**Health hazards** Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

**Environmental hazards** Not Classified

##### Human health

The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

##### Label elements

##### Pictogram



##### Signal word

Danger

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

|                                 |   |
|---------------------------------|---|
| <b>Hazard statements</b>        | <p>H222 Extremely flammable aerosol.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H301 Toxic if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H351 Suspected of causing cancer.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p>  |
| <b>Precautionary statements</b> | <p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P301+P310 If swallowed: Immediately call a poison center/ doctor.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a poison center/ doctor if you feel unwell.</p> |
| <b>Contains</b>                 | Methylene Chloride, Dimethyl Ether  |

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

|   |
|---|
| <b>Methylene Chloride</b> <span style="float: right;"><b>30-60%</b></span><br>CAS number: 75-09-2   |
| <b>Classification</b><br>Acute Tox. 3 - H301<br>Acute Tox. 4 - H312<br>Skin Irrit. 2 - H315<br>Eye Irrit. 2A - H319<br>Carc. 2 - H351<br>STOT SE 3 - H335, H336<br>STOT RE 2 - H373 |
| <b>Dimethyl Ether</b> <span style="float: right;"><b>10-30%</b></span><br>CAS number: 115-10-6  |
| <b>Classification</b><br>Flam. Gas 1 - H220<br>Press. Gas, Liquefied - H280<br>Acute Tox. 4 - H332<br>Skin Irrit. 2 - H315<br>Eye Irrit. 2B - H320<br>STOT SE 3 - H335, H336        |

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

|                            |   |
|----------------------------|---|
| <b>General information</b> | Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.  |
| <b>Inhalation</b>          | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.   |
| <b>Ingestion</b>           | Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.  |
| <b>Skin Contact</b>        | Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.   |
| <b>Eye contact</b>         | Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel. |

### Most important symptoms and effects, both acute and delayed

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.  |
| <b>Ingestion</b>    | Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. |
| <b>Skin contact</b> | May be absorbed through the skin. Product has a defatting effect on skin. The liquid is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.   |
| <b>Eye contact</b>  | Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.   |

## 5. Fire-fighting measures

### Extinguishing media

|                                       |  |
|---------------------------------------|--|
| <b>Suitable extinguishing media</b>   | Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.  |
| <b>Unsuitable extinguishing media</b> | Do not use water jet as an extinguisher, as this will spread the fire. |

### Special hazards arising from the substance or mixture

|                         |   |
|-------------------------|---|
| <b>Specific hazards</b> | Pressurized container: Must not be exposed to temperatures above 50°C/120°F. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. |
|-------------------------|---|

### Advice for firefighters

|  |   |
|--|---|
| <b>Special protective equipment for firefighters</b> | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. |
|--|---|

## 6. Accidental release measures

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

## 8. Exposure Controls/personal protection

### Control parameters

### Occupational exposure limits

#### **Methylene Chloride**

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

#### **Dimethyl Ether**

Long-term exposure limit (8-hour TWA): WEEL:US.AIHA = Workplace Environmental Exposure Level Guides 1000 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

### Exposure controls

#### **Protective equipment**



## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

|   |   |
|---|---|
| <b>Appropriate engineering controls</b> | This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist. |
| <b>Eye/face protection</b>              | Wear chemical splash goggles.   |
| <b>Hand protection</b>                  | Use protective gloves.  |
| <b>Other skin and body protection</b>   | Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.   |
| <b>Hygiene measures</b>                 | DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.   |
| <b>Respiratory protection</b>           | If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.   |

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

|   |  |
|---|--|
| <b>Appearance</b>                                   | Aerosol.   |
| <b>Color</b>  | Clear. Blue.   |
| <b>Odor</b>   | Organic solvents.  |
| <b>Initial boiling point and range</b>              | Not determined.  |
| <b>Flash point</b>                                  | -41°C/-42°F Not specified.   |
| <b>Upper/lower flammability or explosive limits</b> | Lower flammable/explosive limit: 3.4 g/100 g Upper flammable/explosive limit: 18 g/100 g |
| <b>Vapor pressure</b>                               | Not determined.  |
| <b>Vapor density</b>                                | Not determined.  |
| <b>Relative density</b>                             | 1.22   |
| <b>Solubility(ies)</b>                              | Negligibly soluble in water  |
| <b>Volatile organic compound</b>                    | This product contains a maximum VOC content of 99.6 g/l.                                 |

### 10. Stability and reactivity

|   |  |
|---|--|
| <b>Stability</b>                          | Stable at normal ambient temperatures and when used as recommended.  |
| <b>Possibility of hazardous reactions</b> | Will not polymerize.   |
| <b>Conditions to avoid</b>                | Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents. |
| <b>Materials to avoid</b>                 | None known.  |

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

**Hazardous decomposition products** Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Aldehydes. Hydrocarbons.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 173.61111111

##### Acute toxicity - dermal

ATE dermal (mg/kg) 1,909.72222222

##### Acute toxicity - inhalation

ATE inhalation (gases ppm) 31,034.48275862

ATE inhalation (vapours mg/l) 19.09722222

#### Toxicological information on ingredients.

#### Methylene Chloride

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 52.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

##### Carcinogenicity

**Carcinogenicity** Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies

**Target organ for carcinogenicity** Tumerigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors

**IARC carcinogenicity** IARC Group 2B Possibly carcinogenic to humans.

**NTP carcinogenicity** Reasonably anticipated to be a human carcinogen.

##### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness

##### Specific target organ toxicity - repeated exposure

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

**STOT - repeated exposure** Inhalation - May cause damage to organs through prolonged or repeated exposure  
 -Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure  
 -Liver, blood.

**General information** RTECS: PA8050000

### Dimethyl Ether

#### Acute toxicity - inhalation

**Acute toxicity inhalation** 308.5  
 (LC<sub>50</sub> gases ppmV)

**Species** Rat

**ATE inhalation (gases** 4,500.0  
 ppm)

#### Carcinogenicity

**Carcinogenicity** Does not contain any substances known to be carcinogenic.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause respiratory irritation. Central nervous system depression. Skin and eye irritation.

#### Aspiration hazard

**Aspiration hazard** No data available.

**Medical Symptoms** Central nervous system depression. Frostbite. Respiratory system irritation. Skin irritation. Eye irritation.

### 12. Ecological Information

### 13. Disposal considerations

#### Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**Air transport notes** Cargo aircraft only. <75kg

#### UN Number

**UN No. (ICAO)** 3501

**UN No. (DOT)** 3501

#### UN proper shipping name

**Proper shipping name (TDG)** Chemical Under Pressure, Flammable, N.O.S. (Dimethyl Ether)

**Proper shipping name (DOT)** Chemical Under Pressure, Flammable, N.O.S. (Dimethyl Ether)

#### Transport hazard class(es)

**DOT hazard class** 2.1

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

### Transport labels



### Packing group

Not applicable.

## 15. Regulatory information

### US Federal Regulations

#### CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Present.

*Methylene Chloride*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

#### SARA 313 Emission Reporting

Present.

*Methylene Chloride*

0.1 %

#### SARA (311/312) Hazard Categories

Present.

*Dimethyl Ether*

Acute  
Health hazard  
Pressure  
Fire  
Hazard

*Methylene Chloride*

Acute  
Health hazard  
Chronic  
Health hazard

### US State Regulations

#### California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

*Dimethyl Ether*

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

*Methylene Chloride*

Known to the State of California to cause cancer.

#### Massachusetts "Right To Know" List

Present.

*Dimethyl Ether*

Present

*Methylene Chloride*

All the ingredients are listed or exempt.

#### Minnesota "Right To Know" List



## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

*Dimethyl Ether*

Present.

### New Jersey "Right To Know" List

Present.

*Dimethyl Ether*

Present.

*Methylene Chloride*

All the ingredients are listed or exempt.

### Pennsylvania "Right To Know" List

Present.

*Dimethyl Ether*

Present.

*Methylene Chloride*

All the ingredients are listed or exempt.

### Inventories

#### Canada - DSL/NDSL

DSL

*Dimethyl Ether*

#### US - TSCA

Present.

*Dimethyl Ether*

*Methylene Chloride*

### 16. Other information

|                                  |  |
|----------------------------------|--|
| <b>Revision date</b>             | 8/21/2017  |
| <b>Revision</b>                  | 6  |
| <b>Supersedes date</b>           | 4/3/2017   |
| <b>SDS No.</b>                   | 20601  |
| <b>Hazard statements in full</b> | H220 Extremely flammable gas.<br>H222 Extremely flammable aerosol.<br>H280 Contains gas under pressure; may explode if heated.<br>H301 Toxic if swallowed.<br>H312 Harmful in contact with skin.<br>H315 Causes skin irritation.<br>H319 Causes serious eye irritation.<br>H320 Causes eye irritation.<br>H332 Harmful if inhaled.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H351 Suspected of causing cancer.<br>H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure. |
| <b>ACA HMIS Health rating.</b>   | Serious hazard. (3)  |

## Tensorgrip L12 High-Build, High-Strength Web Spray Adhesive

|   |                      |
|---|----------------------|
| <b>ACA HMIS Flammability rating.</b>        | Ignites easily. (3)  |
| <b>ACA HMIS Physical hazard rating.</b>     | Normally stable. (0) |
| <b>ACA HMIS Personal protection rating.</b> | B                    |

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application