

L17N FIRE RATED NON-FLAM CONTACT ADHESIVE


DATA SHEET
TensorGrip®



FRL



Standard Laminate



Metal/Aluminum Sheeting



FRP/GRP



FR-1



As part of our **WOODWORKING** range, **L17N** is a web spray adhesive designed for use in fabricating countertops, cabinets and doors using the substrates listed above.

PRODUCT DESCRIPTION

TensorGrip® L17N is a high performance fire rated, non-flammable industrial spray contact adhesive formulated for bonding decorative HPL (high pressure laminate) to a variety of substrates. Outstanding bond to Fire Retardant MDF. Tested for Fire Resistance.

ADVANTAGES

- Fire rated (BS 476: Part 7: 1997, Class 1)
- Completely non-flammable
- No VOCs
- Excellent high coverage
- 80% of final strength achieved immediately
- Full strength achieved in 24 hours
- High tack
- Fast drying with long open time
- Excellent green strength
- High heat resistance
- Over 220°F (105°C) temperature resistant
- No ODS (Ozone Depleting Substances)

DIRECTIONS FOR USE

- **TensorGrip® L17N** is designed as a portable, self-contained spray system for field or shop applications.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60° F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

If canister will be unused for longer than 2 weeks, shut canister valve off and drain hose to prevent buildup of adhesive.

CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.

QUIN GLOBAL US

5710 F ST. Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quin-global.com

QUIN
GLOBAL

TensorGrip®

LI7N FIRE RATED NON-FLAM CONTACT ADHESIVE

DATA SHEET
Tensorgrip[®]

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

- | | |
|-----------------------|---------------------------------------|
| • Total Solids | 21-27% |
| • VOC Content | 0 g/L |
| • Color | Clear or Quin Blue |
| • System Flammability | 100% Non-Flammable |
| • Solvent System | Methylene Chloride |
| • Dry time | 2-4 mins dependent on temp & humidity |
| • Open time | Long |
| • Shelf Life | 18 months from date of manufacture |

PACKAGING

- | | |
|--------|---------------------|
| • 22L | Disposable Canister |
| • 108L | Returnable Canister |
| • 216L | Returnable Canister |

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com

QUIN
GLOBAL

Tensorgrip[®]