

# SAFETY DATA SHEET Tensorgrip M31 Super High Strength Infusion RTM

### 1. Identification

**Product identifier** 

Product name Tensorgrip M31 Super High Strength Infusion RTM

Product number USA

Recommended use of the chemical and restrictions on use

**Application** Canister Spray Adhesive

Details of the supplier of the safety data sheet

**Supplier** Quin Global

5710 F St (402) 731 3636 (402) 731 1473

marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A

- H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373

**Environmental hazards** Aquatic Chronic 3 - H412

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

**Pictogram** 





Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Contains Methyl Acetate, n-Hexane

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### **Substances**

### **Mixtures**

Methyl Acetate	30-60%
CAS number: 79-20-9	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	

### Tensorgrip M31 Super High Strength Infusion RTM

n-Hexane 10-30%

CAS number: 110-54-3 M factor (Acute) = 1

### Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Aquatic Chronic 2 - H411

The Full Text for all Hazard Statements are Displayed in Section 16.

### 4. First-aid measures

### Description of first aid measures

General information Remove affected person from source of contamination. Place unconscious person on their

side in the recovery position and ensure breathing can take place. Get medical attention if any

discomfort continues.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

**Ingestion** Get medical attention immediately. Never give anything by mouth to an unconscious person.

Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a

position comfortable for breathing.

**Skin Contact** Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the

person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get

medical attention promptly. Show this Safety Data Sheet to the medical personnel.

### Most important symptoms and effects, both acute and delayed

Inhalation May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The liquid is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

### Tensorgrip M31 Super High Strength Infusion RTM

### Eye contact

Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

### 5.Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers

can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source

of ignition and flash back.

### Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of

ignition near spillage.

**Environmental precautions** 

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

### Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and

place into containers. Wash thoroughly after dealing with a spillage.

### 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide

adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the

ground.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container. Pressurized container: Must not be exposed to temperatures above

50°C/120°F

### Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### 8. Exposure Controls/personal protection

### **Control parameters**

### Occupational exposure limits

#### **Methyl Acetate**

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm Short-term exposure limit (15-minute): ACGIH 250 ppm

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m<sup>3</sup>

#### n-Hexane

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

Sk

Ceiling Value: OSHA\_TRANS 500 ppm 1800 mg/m3

Long-term exposure limit (8-hour TWA): OSHA 50 ppm 180 mg/m³ ACGIH = American Conference of Governmental Industrial Hygienists.

Sk = Danger of cutaneous absorption.

OSHA = Öccupational Safety and Health Administration.

#### **Exposure controls**

### Protective equipment





## Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

**Eye/face protection** Wear chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level

exposures, a supplied air respirator should be used.

### 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance Aerosol.

Color Clear Red.

Odor Characteristic.

Initial boiling point and range 57.5°C (135°F)

### Tensorgrip M31 Super High Strength Infusion RTM

Flash point -25.99°C/-14.78°F CC (Closed cup).

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 16 g/100 g Lower flammable/explosive limit: 1.2 g/100 g

Relative density 0.88

Solubility(ies) Insoluble in water

Volatile organic compound This product contains a maximum VOC content of 180 g/l.

10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Oxidizing agents. Reducing agents.

Materials to avoid Strong Oxidizers.

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

Hydrogen chloride (HCI). Nitrous gases (NOx).

### 11. Toxicological information

### Information on toxicological effects

Acute toxicity - oral

**ATE oral (mg/kg)** 717.15

Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,577.74

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 15.78

Toxicological information on ingredients.

### **Methyl Acetate**

Acute toxicity - oral

Acute toxicity oral (LD50

5,000.0

mg/kg)

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.0

mg/kg)

Species Rat

**ATE dermal (mg/kg)** 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation 49.28

(LC50 vapours mg/l)

**Species** Rat

### Tensorgrip M31 Super High Strength Infusion RTM

ATE inhalation (vapours

mg/l)

n-Hexane

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

25,000.0

11.0

**Species** Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.0

mg/kg)

**Species** Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC<sub>50</sub> vapours mg/l)

171.6

**Species** Rat

ATE inhalation (vapours

11.0

mg/l)

Reproductive toxicity

Reproductive toxicity -

Suspected of damaging fertility.

fertility

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness

**Target organs** Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

**Target organs** Central nervous system

Aspiration hazard

Aspiration hazard Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

General information After absorption. Tiredness. Narcosis. After long term exposure to the chemical:

CNS disorders, paralysis symptoms. (It generally applies to aliphatic hydrocarbons

with 6 - 18 carbon atoms that they cause pneumonia, in some cases also pulmonary edema, upon direct inhalation, i.e. in conditions that can occur only in

very special circumstances (nebulizations, spraying, inhalation of aerosols and similar.)) Absorbtion of large quantities may cause: Narcosis. Possible risk of

adverse reproductive effects.

Inhalation May cause drowsiness or dizziness. Vapors irritate the respiratory system.

**Ingestion** Irritating. May cause nausea, stomach pain and vomiting.

**Skin Contact** The product is irritating to eyes and skin.

**Eye contact** Risk of corneal clouding.

Route of entry Inhalation Skin and/or eye contact

Target Organs Eyes Skin Respiratory system, lungs Central nervous system Peripheral nervous

system

### 12. Ecological Information

### 13. Disposal considerations

### Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

### 14. Transport information

Air transport notes Cargo aircraft only. <75kg

**UN Number** 

**UN No. (DOT)** 3501 **UN No. (ICAO)** 3501

UN proper shipping name

Proper shipping name (DOT) Chemical Under Pressure, Flammable, N.O.S. (Methyl Acetate, n-Hexane)

Transport hazard class(es)

DOT hazard class 2.1

### Transport labels



### Packing group

Not applicable.

### 15. Regulatory information

### **US Federal Regulations**

### CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

### n-Hexane

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

### SARA 313 Emission Reporting

The following ingredients are listed or exempt:

#### n-Hexane

100%

### SARA (311/312) Hazard Categories

Hazard

### **Methyl Acetate**

Fire Acute Chronic Health hazard

### n-Hexane

Acute Chronic Health hazard Fire

### **US State Regulations**

### California Proposition 65 Carcinogens and Reproductive Toxins

Ths product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

### Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

### **Methyl Acetate**

Present

### n-Hexane

Present

### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

### **Methyl Acetate**

Present.

### n-Hexane

Present.

### Inventories

### Canada - DSL/NDSL

The following ingredients are listed or exempt:

### **Methyl Acetate**

Present.

### n-Hexane

DSL

### US - TSCA

The following ingredients are listed or exempt:

### **Methyl Acetate**

Present.

#### n-Hexane

Present.

### 16. Other information

### Revision date

2/18/2016

### Tensorgrip M31 Super High Strength Infusion RTM

Revision 1

 Supersedes date
 2/18/2016

 SDS No.
 21549

Hazard statements in full H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

ACA HMIS Health rating. Slight hazard. (1)

**ACA HMIS Flammability** 

rating.

Extremely flammable. (4)

ACA HMIS Physical hazard

rating.

Normally stable. (0)

ACA HMIS Personal protection rating.

В

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application