



SAFETY DATA SHEET

Tensorgrip M80 High Temp Contact Adhesive

1. Identification

Product identifier

Product name Tensorgrip M80 High Temp Contact Adhesive

Product number USA

Recommended use of the chemical and restrictions on use

Application Canister Spray Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global
5710 F St
(402) 731 3636
(402) 731 1473
marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Acute Tox. 3 - H301 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

Environmental hazards Not Classified

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram



Signal word

Danger

Tensorgrip M80 High Temp Contact Adhesive

Hazard statements	<p>H222 Extremely flammable aerosol.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H301 Toxic if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H351 Suspected of causing cancer.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p>
Precautionary statements	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P261 Avoid breathing vapor/ spray.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a poison center/ doctor if you feel unwell.</p>
Supplemental label information	AT(o) 15.0% of the mixture consists of ingredient(s) of unknown acute oral toxicity.
Contains	Methylene Chloride, Propane, Isobutane

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Methylene Chloride 30-60% CAS number: 75-09-2
Classification Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Unknown Classification Unknown Classification Unknown Classification Carc. 2 - H351 Unknown Classification STOT SE 3 - H335, H336 STOT RE 2 - H373
Isobutane 10-30% CAS number: 75-28-5
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280 Unknown Classification

Tensorgrip M80 High Temp Contact Adhesive

Propane	10-30%
CAS number: 74-98-6	
Classification	
Flam. Gas 1 - H220	
Press. Gas, Liquefied - H280	
Acute Tox. 4 - H332	
Simple Asphyxiant - USH03	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

General information	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
Ingestion	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Prolonged or repeated exposure may cause the following adverse effects: Irritation and redness, followed by blurred vision.

Indication of immediate medical attention and special treatment needed

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Tensorgrip M80 High Temp Contact Adhesive

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm
A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

Tensorgrip M80 High Temp Contact Adhesive

Isobutane

Long-term exposure limit (8-hour TWA): ACGIH 1000 ppm

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 800 ppm 1900 mg/m³

Propane

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 1800 mg/m³ 1000 ppm

Long-term exposure limit (8-hour TWA): OSHA 1800 ppm 1000 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Clear Red. Green.
Odor	Organic solvents.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapor density	Not determined.
Relative density	1.22
Solubility(ies)	Negligibly soluble in water

Tensorgrip M80 High Temp Contact Adhesive

Volatile organic compound This product contains a maximum VOC content of 160.5 g/l.

10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.

Materials to avoid Strong oxidizing agents. Aluminum. Magnesium. Amines. Strong alkalis.

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Aldehydes. Hydrocarbons.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 160.08

Acute toxicity - dermal

ATE dermal (mg/kg) 2,071.56

Acute toxicity - inhalation

ATE inhalation (gases ppm) 30,000.0

ATE inhalation (vapours mg/l) 73.33

Toxicological information on ingredients.

Methylene Chloride

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 52.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

Carcinogenicity

Tensorgrip M80 High Temp Contact Adhesive

Carcinogenicity	Carcinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies
Target organ for carcinogenicity	Tumorigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors
IARC carcinogenicity	IARC Group 2B Possibly carcinogenic to humans.
NTP carcinogenicity	Reasonably anticipated to be a human carcinogen.

Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Inhalation - May cause damage to organs through prolonged or repeated exposure
-Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure
-Liver, blood.

General information RTECS: PA8050000

Isobutane

Toxicological effects No information available.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Inhalation Suffocation (asphyxiant) hazard

Skin Contact Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Eye contact Spray will evaporate and cool quickly and may cause frostbite or cold burns if in contact with skin.

Propane

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 1,442.0

Species Rat

Acute toxicity inhalation (LC₅₀ vapours mg/l) 1,442.0

Species Rat

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

12. Ecological Information

Toxicity

Tensorgrip M80 High Temp Contact Adhesive

Persistence and degradability

Bioaccumulative potential

Mobility in soil

Results of PBT and vPvB assessment

Other adverse effects

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

Air transport notes Cargo aircraft only. <75kg

UN Number

UN No. (TDG) 3501

UN No. (ICAO) 3501

UN No. (DOT) 3501

UN proper shipping name

Proper shipping name (TDG) Chemical Under Pressure, Flammable, N.O.S.

Proper shipping name (DOT) Chemical Under Pressure, Flammable, N.O.S.

Transport hazard class(es)

TDG class 2

TDG label(s) 2.1

Transport labels



Packing group

Not applicable.

Environmental hazards

Special precautions for user

15. Regulatory information

International Regulations

US Federal Regulations

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)
Present.

Methylene Chloride

Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA 313 Emission Reporting

Present.

Tensorgrip M80 High Temp Contact Adhesive

Methylene Chloride

0.1 %

SARA (311/312) Hazard Categories

Present.

Isobutane

Fire
Pressure
Hazard

Propane

Yes.

Methylene Chloride

Acute
Health hazard
Chronic
Health hazard

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Present.

Isobutane

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

Methylene Chloride

Known to the State of California to cause cancer.

Massachusetts "Right To Know" List

Present.

Isobutane

Propane

Methylene Chloride

New Jersey "Right To Know" List

Present.

Isobutane

Propane

Methylene Chloride

Pennsylvania "Right To Know" List

Present.

Isobutane

Propane

Methylene Chloride

Inventories

Canada - DSL/NDSL

Present.

Propane

US - TSCA

Present.

Tensorgrip M80 High Temp Contact Adhesive

Methylene Chloride

16. Other information

Revision date	11/1/2016
Revision	4
Supersedes date	5/6/2016
SDS No.	20482
Hazard statements in full	<p>H220 Extremely flammable gas. H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. USH03 May displace oxygen and cause rapid suffocation</p>
ACA HMIS Health rating.	Moderate hazard. (2)
ACA HMIS Flammability rating.	Ignites easily. (3)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	B

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application