MOB GENERAL PURPOSE MARINE SPRAY ADHESIVE

DATA SHEET Tensor



As part of our MARINE range, M88 is a mist spray adhesive designed as a general purpose adhesive that can be used on many different substrates including foam, leather and fabric.

PRODUCT DESCRIPTION

TensorGrip® M88 is an industrial strength general purpose spray adhesive designed for permanent or temporary bonds. Perfect for marine seating and interior boat walls.

ADVANTAGES

- Temporary or permanent bonds
- Fast drying with excellent intial bond
- Multi-purpose so it works on a variety of substrates
- Mist spray virtually eliminates telegraphing

DIRECTIONS FOR USE

- TensorGrip[®] M88 is designed as a portable, selfcontained spray system for field or shop applications.
- Apply adhesive to one or both surfaces to be mated, at 80% to 100% coverage. Spraying both surfaces will result in a stronger, more permanent bond.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60° F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117 PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com



Tensorgrip

GENERAL PURPOSE MARINE SPRAY ADHESIVE

DATA SHEET Tensor

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

- Total Solids
- VOC Content
- Color
- System Flammability
- Solvent System
- Shelf Life

PACKAGING

- 650ml
- 7L
- 22L

25-31% 340g/L Red, Clear Flammable adhesive; Flammable propellant Methyl Acetate 18 months from date of manufacture

Aerosol Cans Disposable Canister Disposable Canister

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

QUIN GLOBAL US

5710 F ST. Omaha NE 68117 PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com



